

# AsteRx-i3 D Pro+

GNSS/INS for integrated solutions, ready for sensor fusion



**AsteRx-i3 D Pro+ delivers reliable centimeter level positioning combined with 3D orientation in demanding environments. Its onboard inertial sensor provides orientation and positional dead-reckoning, making it ideal for systems that require continuous positioning even during short GNSS outages. AsteRx-i3 D Pro+ is the most flexible GNSS/INS solution offering full access to raw GNSS and INS data and allowing multiple antenna configurations.**

## KEY FEATURES

- ▶ **Centimeter-level GNSS positioning enhanced by an IMU and optionally vehicle velocity**
- ▶ **Full access to raw GNSS and IMU data**
- ▶ **Heading, pitch and roll on a single antenna for the most compact system**
- ▶ **Heading available immediately from initialization with dual antenna configuration**
- ▶ **Lightweight, low power and compact**
- ▶ **AIM+ advanced anti-jamming, anti-spoofing monitoring and mitigation technology, as part of the GNSS+ algorithm suite**

## Reliable and robust

The AsteRx-i3 D Pro+ is a state-of-the-art GNSS/INS rover receiver designed to provide robust and reliable positioning and 3D attitude in the most challenging environments. Septentrio's multi-constellation, multi-frequency, accurate and reliable RTK is enhanced by a powerful GNSS/INS integration accurately measuring heading, pitch and roll. While a single antenna allows a lean configuration, the dual antenna enables heading measurement without the need for movement. AsteRx-i3 D Pro+ features Advanced Interference Mitigation (AIM+ ) technology which can suppress the widest variety of interferers, from simple continuous narrowband signals to the most complex wideband and pulsed jammers.

## Ideal for any integration

The AsteRx-i3 D Pro+ is not only delivering an already integrated position, but it also provides raw GNSS and IMU data, already synchronized and in a single data stream for customers that will integrate those components with other sensors for a larger data fusion system (i.e. lidar). Having GNSS and IMU hardware already integrated and data streams already synchronized enables users to focus on their own core technology without having to integrate GNSS and IMU sensors themselves.

## Easy to integrate

The AsteRx-i3 D Pro+ delivers a full INS system on a single board for the maximum ease of hardware integration. Septentrio's web interface, software tools such as lever arm optimization and support material found in the Knowledge Base make the integration process easy and fast.

# AsteRx-i3 D Pro+

## FEATURES

### GNSS signals

544 Hardware channels for simultaneous tracking of most visible signals:

- ▶ GPS: L1 C/A, L1C, L2C, L2 P, L5
- ▶ GLONASS: L1 C/A, L2C/A
- ▶ BeiDou: B1I, B2I, B3I
- ▶ Galileo: E1, E5a, E5b, E5 AltBOC
- ▶ QZSS: L1C/A; L2C; L5
- ▶ SBAS: EGNOS, WAAS, GAGAN, MSAS, SDCM

### Septentrio's patented GNSS+ technologies

- ▶ **AIM+** industry leading anti-jamming, anti-spoofing interference monitoring & mitigation technology
- ▶ **FUSE+** fusion of RTK positioning with an inertial sensor and more
- ▶ **IONO+** advanced scintillation mitigation
- ▶ **APME+** a posteriori multipath estimator for code and phase multipath mitigation
- ▶ **LOCK+** superior tracking robustness under heavy mechanical shocks or vibrations
- ▶ **RAIM+** (Receiver Autonomous Integrity Monitoring)

### Formats

Septentrio Binary Format (SBF), fully documented with sample parsing tools  
 NMEA 0183, v3.01, v4.0  
 RTCM v2.x, v3.x (MSM messages included)  
 CMR v2.0 and CMR+

### Connectivity

4 Hi-speed serial ports (LVTTTL)  
 1 USB device port (TCP/IP communication and with 2 extra serial ports)  
 xPPS output (max 100Hz)  
 Ethernet port (TCP/IP, UDP, LAN 10/100 Mbps)  
 2 Event markers  
 Outputs to drive external LEDs  
 General purpose output  
 NTRIP (client)

### Dead reckoning positioning and attitude accuracy<sup>2,8</sup>

#### GNSS/INS

Duration (s)	Horizontal (m)	Vertical (m)	Heading (deg)	Pitch/roll (deg)
5	0,106	0,04	0,35	0,04
10	0,306	0,06	0,35	0,06
30	3,006	0,25	0,4	0,1

## PERFORMANCE

### Integrated position accuracy<sup>1,2</sup>

	Horizontal	Vertical
Standalone	1.2 m	1.9 m
SBAS	0.6 m	0.8 m
DGPS	0.4 m	0.7 m

### RTK-INS<sup>1,2,3</sup>

Horizontal accuracy	0.6 cm + 0.5 ppm	
Vertical accuracy	1 cm + 1 ppm	
Initialisation	7 s	

### Integrated attitude accuracy<sup>1,2,3</sup>

	Non RTK mode	RTK mode
Heading, dual antenna	0.3°	0.15°
Heading, single antenna	0.3°	0.2°
Pitch/roll, dual antenna	0.04°	0.02°

### INS velocity<sup>1,2,3</sup>

	Non RTK mode	RTK mode
Velocity	0.05 m/s	0.02 m/s

### IMU performance

#### Gyroscope performance

Input range	± 500°/s
Bias in-run instability	2.7°/hr
Random walk / noise density <sup>4</sup>	0.15 - 0.2°/√hr

#### Accelerometer performance

Input range	±8 g
Bias in-run instability <sup>4</sup>	2.7 - 4.4 µg
Random walk / noise density <sup>4</sup>	17.0 - 24.8 µg/√Hz

### Maximum update rate

Integrated position	100 Hz
Latency <sup>7</sup>	<20 ms
GNSS measurements	2 Hz
IMU raw data	200 Hz

### Time precision

xPPS out	5 ns
Event accuracy	< 20 ns

### Time to first fix

Cold start <sup>5</sup>	< 45 s
Warm start <sup>6</sup>	< 20 s
Re-acquisition avg.	avg 1 s

### Tracking performance (C/N0 threshold)

Tracking	20 dB-Hz
Acquisition	33 dB-Hz

## PHYSICAL AND ENVIRONMENTAL

Size	47.5 × 70 × 10.5 mm 1.87 × 2.75 × 0.41 in
Weight	30 g / 1.06 oz
Input voltage	3.3 VDC ± 5%

### Power consumption

GPS/GLO L1/L2	1.0 W
All signals, all GNSS constellations	1.2 W

### Antenna

Connectors	2 x MMCX
Antenna supply voltage	3-5.5 VDC
Maximum antenna current	150 mA
Antenna gain range	15-45 dB

### I/O connectors

30 Pins Hirose DF40 socket  
 60 Pins Hirose DF40 socket for expanded connectivity

### Environment

Operating temperature	-40° C to +85° C -40° F to +185° F
Storage temperature	-55° C to +85° C -67° F to +185° F
Humidity	5% to 95% (non-condensing)
Vibration	MIL-STD-810G

### Certification

RoHS, WEEE, ISO 9001-2015



<sup>1</sup> Open-sky conditions

<sup>2</sup> RMS levels

<sup>3</sup> Baseline < 40 Km

<sup>4</sup> Z-axis (lower value is for X & Y)

<sup>5</sup> No information available (no almanac, no approximate position)

<sup>6</sup> Ephemeris and approximate position known

<sup>7</sup> 98% of samples

<sup>8</sup> RTK fix before outage

<sup>9</sup> Using high accuracy and low latency velocity input

### EMEA

Greenhill Campus (HQ)  
 Interleuvenlaan 15i  
 3001 Leuven, **Belgium**

Espoo, **Finland**

### Americas

2601 Airport Drive,  
 Suite 360  
 Torrance, CA 90505, **USA**

septentrio.com/contact

### Asia-Pacific

Shanghai, **China**  
 Yokohama, **Japan**  
 Seoul, **Korea**

septentrio.com



septentrio<sup>®</sup>